



Fall protection

MEDBLOC AN13006C2

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Easy to use

· NFC system guarantees traceability



Visibility

· Visual fall indicator for instant verification that the product is working properly

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Oil & Gas (extraction)
- Power Energy
- Storage

Certifications and norms

EN360

RFU 10.060
HORIZONTAL CERTIFICATION
RFU 11.062
128 KG



Protects against risks



Fall



Fall protection

MEDBLOC AN13006C2

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Webbing reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Polyester
Strap width (mm)	25 mm
ARA lenght	6 m
Color	Black
Connector (user side)	Small hook, steel, opening 21 mm
SIZE	6 m
Lifespan from manufacturing	10 years
Weight	1,6 kg
Maximum load for one person	128 kg
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure
ARA lenght	236.2206 inch



Fall protection

MEDBLOC AN13006C2

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN13006C2	Black	6 m	MEDBLOC AN13006C2	3295249264949	13295249264946	5	1	11.7 kg