



Fall protection

HAR22H

FALL ARRESTER HARNESSES

Ergonomic harness for maximum freedom of movement with 2 anchorage points



Specific benefits



Comfort

- Specifically designed leg straps providing freedom of movement for long working days
- Bavarian design adapted to the body shape of women and men



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 150 kg



Easy to use

- Ergonomic design facilitating user movements
- NFC system guarantees traceability

Applications

- Agriculture
- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)

Certifications and norms

EN361

150 KG



Protects against risks



Fall



Fall protection

HAR22H

FALL ARRESTER HARNESSES

Ergonomic harness for maximum freedom of movement with 2 anchorage points

Standards - Details

Technical details

Type of equipment	Fall arrester harness
Composition of the main support	Steel, Polyester
Fastening	Buckles
Total number of attachment points for the fall arrester	2
Buckles	Manual loop
Anti-fall point	Dorsal, Sternal
Color	Black
Lifespan from manufacturing	10 years
Weight	1,2 kg
Number of manual buckles	5
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Long vertical movement or movement on inclined surface, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Sternal	1
Dorsal	1



Fall protection

HAR22H

FALL ARRESTER HARNESSES

Ergonomic harness for maximum freedom of movement with 2 anchorage points

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
-----------	--------	------	-------------	-------	----------	----------------	---------------	--------