



Fall protection

# X-TREM LIGHT HAR22X

## FALL ARRESTER HARNESSES

The lightest innovative harness on the market with no metal parts



### Specific benefits



#### Hygiene

· Harnesses and textiles can be washed with neutral soap



#### Performance

· Certification above the maximum rated load of 100 kg; product certified at 150 kg



#### Easy to use

· Ergonomic design facilitating user movements  
· NFC system guarantees traceability

### Certifications and norms

EN361

150 KG



### Applications

- Agriculture
- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive

### Protects against risks



Fall



# X-TREM LIGHT HAR22X

## FALL ARRESTER HARNESSSES

The lightest innovative harness on the market with no metal parts

Fall protection

### Standards - Details

### Technical details

Type of equipment	Fall arrester harness
Composition of the main support	Steel, Plastic, Polyester
Fastening	Buckles
Total number of attachment points for the fall arrester	2
Buckles	Manual loop
Anti-fall point	Dorsal, Sternal
Color	Black
SIZE	S/M/L
Comfort elements	Plastic back brace
Lifespan from manufacturing	10 years
Weight	0,580 kg
Number of manual buckles	2
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Sternal	1
Dorsal	1



# X-TREM LIGHT HAR22X

## FALL ARRESTER HARNESSES

The lightest innovative harness on the market with no metal parts

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
-----------	--------	------	-------------	-------	----------	----------------	---------------	--------