



Fall protection

# LYNX HAR35R

## FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers



### Specific benefits



#### Comfort

- 3D comfort foam integrated into harnesses, providing comfort and breathability for extended use
- Thermoformed belt for optimal lumbar support and comfort



#### Hygiene

- Harnesses and textiles can be washed with neutral soap



#### Performance

- Certification above the maximum rated load of 100 kg; product certified at 150 kg



#### Easy to use

- Ergonomic design facilitating user movements
- NFC system guarantees traceability

### Applications

- Public works
- Finishing works / Craftsmanship
- Chemical industry
- Automotive
- Oil & Gas (extraction)
- Mining

### Certifications and norms

EN361

150 KG



EN813

150 KG

EN358

### Protects against risks



Fall



Fall protection

# LYNX HAR35R

## FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

### Standards - Details

### Technical details

Color	Grey-Yellow
Composition of the main support	Aluminum, Polyester
Comfort elements	"Soft padding" on shoulders and thigh strap, Thermocompressed back and shorts
Lifespan from manufacturing	10 years
Total number of attachment points for the fall arrester	2
Number of total holding attachment points	2
Anti-fall point	Dorsal, Sternal
Suspension point	Ventral
Holding point	Belt
Nombre de points d'accroche de suspension	1
Fastening	Buckles
Number of non-removable buckles	4
Weight	2,5 kg
Type of equipment	Fall arrester harness with belt
Number of manual buckles	2
Number of automatic loops	2
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Sternal	1
Dorsal	1



Fall protection

# LYNX HAR35R

## FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
-----------	--------	------	-------------	-------	----------	----------------	---------------	--------