



Fall protection

PROTECTOR ELEVATOR TR01820U

RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery



Specific benefits



Comfort

- Double swivel for optimum user tracking



Performance

- Certification above the maximum rated load of 100 kg; product certified at 150 kg



Easy to use

- End handle for easy cable winding
- Carrying handle for easy transport
- NFC system guarantees traceability



Durability

- Impact-resistant ABS housing

Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Certifications and norms

EN360

RFU 11.062
150 KG



EN1496

CLASS A
150 KG

Protects against risks



Fall



Fall protection

PROTECTOR ELEVATOR TR01820U

RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery

Standards - Details

Technical details

Type of equipment	Cable reel, winch function
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Stainless steel
ARA lenght	20 m
Length	20m
Cable diameter	5 mm
Included elements	Included energy absorber
Color	Black-Orange
Connector (user side)	Small hook, steel, opening 21 mm
Lifespan from manufacturing	20 years
Weight	13,9 kg
Maximum load for one person	150 kg
Fall arrest work situations	Rescue and evacuation, Vertical movement, confined space
Locking system	Inertia locking system
ARA lenght	787.402 inch



PROTECTOR ELEVATOR TR01820U

RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
TR01820U	Black-Orange	20 m	PROTECTOR ELEVATOR TR01820U	3295249254704	13295249254701	1	1	14.7 kg