



Fall protection

# PROTECTOR ELEVATOR TR01830U

RETRACTABLE FALL ARRESTERS

30 metre self retractable fall arrester with rescue option for victim recovery



## Specific benefits



### Comfort

- Double swivel for optimum user tracking



### Performance

- Certification above the maximum rated load of 100 kg; product certified at 150 kg
- Double swivel design for optimum user tracking and improved rewinding of the strap in the housing



### Easy to use

- Automatic carabiners for secure and time-saving locking
- End handle for easy cable winding
- Carrying handle for easy transport

## Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

## Certifications and norms

### EN360

RFU 11.062  
150 KG



### EN1496

CLASS A  
150 KG

## Protects against risks



Fall



Fall protection

# PROTECTOR ELEVATOR TR01830U

## RETRACTABLE FALL ARRESTERS

30 metre self retractable fall arrester with rescue option for victim recovery

### Standards - Details

### Technical details

Type of equipment	Cable reel, winch function
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Stainless steel
ARA length	30 m
Cable diameter	5 mm
Included elements	Included energy absorber
Color	Black-Orange
Connector (user side)	Small hook, steel, opening 21 mm
Lifespan from manufacturing	20 years
Weight	14,5 kg
Maximum load for one person	150 kg
Fall arrest work situations	Rescue and evacuation, Vertical movement, confined space
Locking system	Inertia locking system
ARA length	1181.103 inch



# PROTECTOR ELEVATOR TR01830U

## RETRACTABLE FALL ARRESTERS

30 metre self retractable fall arrester with rescue option for victim recovery

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
TR01830U	Black-Orange	30 m	PROTECTOR ELEVATOR TR01830U	3295249254711	13295249254718	1	1	15.3 kg