



Hand protection

# PICAFLOR VE240

WORK WITH OCCASIONAL CHEMICAL RESISTANCE

Chemical glove, ideal for the food industry



## Specific benefits



### Durability

· High-quality coating extends the life of the glove and provides excellent protection for the hand



### Performance

· Lightweight for optimal dexterity

## Applications

- Agriculture
- Public works
- Finishing works / Craftsmanship
- Manufacturing/Transformation
- Accommodation & Food services
- Maintenance

## Certifications and norms



EN ISO 374-5



EN ISO 374-1

TYPE B  
K (SODIUM HYDROXIDE 40%)L (SULPHURIC ACID 96%)M (NITRIC ACID 65%)P (HYDROGEN PEROXIDE 30%)T (FORMALDEHYDE 37%)



## Protects against risks



Biological



Chemical



Particules



*enjoy safety.*

Edit 12/11/2023  
www.deltaplus.eu



Hand protection

# PICAFLOR VE240

WORK WITH OCCASIONAL CHEMICAL RESISTANCE

Chemical glove, ideal for the food industry

## Standards - Details



### EN388:2016+A1:2018

1 [0-4] ABRASION RESISTANCE  
0 [0-5] CUT RESISTANCE  
1 [0-4] TEAR RESISTANCE  
0 [0-4] PIERCE RESISTANCE  
X [A-F] CUT RESISTANCE ISO 13997



### EN 374

K (SODIUM HYDROXIDE 40%) : SODIUM HYDROXIDE 40%  
L (SULPHURIC ACID 96%) : SULPHURIC ACID 96%  
M (NITRIC ACID 65%) : NITRIC ACID 65%  
P (HYDROGEN PEROXIDE 30%) : HYDROGEN PEROXIDE 30%  
T (FORMALDEHYDE 37%) : FORMALDEHYDE 37%

## Technical details

Glove kind	Tight glove
Glove family	Tight glove unsupported flocked
Tight glove kind	Unsupported
Inner finition	Flocked
Coating material and finition	Latex pattern
Coating level	Fully coated
Number of layer	Single layer
Thickness	0,38 mm
Arm level protection	Forearm cuff (< 400mm)
Color	Yellow
Size	6, 7, 8, 9, 10
Type of packaging	Sold individually



Safety gloves

# PICAFLOR VE240

WORK WITH OCCASIONAL CHEMICAL RESISTANCE

Chemical glove, ideal for the food industry

## Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
-----------	--------	------	-------------	-------	----------	----------------	---------------	--------