



Hand protection

VENICUTC02

SLIGHTLY SHARP AND LONG-LASTING WORK

Level C cut-resistant glove with padding for extra durability, ideal in dry conditions



Specific benefits



Hygiene

- Reduces perspiration thanks to its excellent breathability



Performance

- Lightweight for optimal dexterity
- The anti-slip properties of the polyurethane coating provides good grip.
- SOFTnocut fiber provides excellent cut resistance

Applications

- **Public works**
- **Building**
- **Finishing works / Craftsmanship**
- **Maintenance**
- **Automotive**
- **Mining**

Certifications and norms



ANSI ISEA 105
A3

Protects against risks



Cutting



Wearing



enjoy safety.

Edit 13/11/2023
www.deltaplus.eu



Hand protection

VENICUTC02

SLIGHTLY SHARP AND LONG-LASTING WORK

Level C cut-resistant glove with padding for extra durability, ideal in dry conditions

Standards - Details



EN388:2016+A1:2018

4 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
3 [0-4] PIERCE RESISTANCE
C [A-F] CUT RESISTANCE ISO 13997

Technical details

| | |
|-------------------------------|--|
| Glove kind | Mechanical glove |
| Glove family | Knitted coated glove |
| Mechanical glove kind | Knitted |
| Coating material and finition | PU |
| Coating level | Palm coated |
| Number of layer | Single layer |
| Gauge | 15 |
| Cuff characteristic | Long cuff |
| Cuff length | 100 mm |
| Benefits element | Reach, Vendor pack, Long cuff (>290mm) |
| Color | Grey |
| Size | 7, 8, 9, 10, 11 |
| Type of packaging | Sold individually |



Safety gloves

VENICUTC02

SLIGHTLY SHARP AND LONG-LASTING WORK

Level C cut-resistant glove with padding for extra durability, ideal in dry conditions

Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code | Multiple sales | Minimum sales | Weight |
|-----------|--------|------|-------------|-------|----------|----------------|---------------|--------|
|-----------|--------|------|-------------|-------|----------|----------------|---------------|--------|