

CHEMSAFE VV835

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove combining comfort of use and prolonged use against hydrocarbons



Specific benefits



Durability

· Longer service life thanks to a double coating for excellent abrasion resistance



Hygiene

- · Latex-free to reduce the risk of allergies
- · Nitrile means no risk of allergies for users



Performance

• The nitrile coating gives people working in oily/greasy environments an excellent grip on the objects they handle

Applications

- Public works
- Building
- Maintenance
- Chemical industry
- Automotive
- Oil & Gas (extraction)

Certifications and norms





EN 388

4121X



EN ISO 374-5



EN ISO 374-1

TYPE B A (METHANOL)J (N-HEPTANE)K (SODIUM HYDROXIDE 40%)L (SULPHURIC ACID 96%)

Protects against risks















CHEMSAFE VV835

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove combining comfort of use and prolonged use against hydrocarbons

Standards - Details



EN388:2016+A1:2018

4 [0-4] ABRASION RESISTANCE 1 [0-5] CUT RESISTANCE 2 [0-4] TEAR RESISTANCE 1 [0-4] PIERCE RESISTANCE X [A-F] CUT RESISTANCE ISO 13997



EN 374

A (METHANOL): MÉTHANOL
J (N-HEPTANE): N-HEPTANE

K (SODIUM HYDROXIDE 40%) : SODIUM

HYDROXIDE 40%

L (SULPHURIC ACID 96%): SULPHURIC ACID

96%

Technical details

Glove kind	Tight glove
Glove family	Tight glove supported
Tight glove kind	Supported
Coating material and finition	Triple coating nitrile foam
Coating level	Fully coated
Number of layer	Triple layer
Thickness	1,15 mm
Gauge	18
Arm level protection	Forearm cuff (< 400mm)
Benefits element	Reach, Free latex, Vendor pack, Long cuff (>290mm)
Color	Green
Size	8, 9, 10, 11
Type of packaging	Sold individually







CHEMSAFE VV835

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove combining comfort of use and prolonged use against hydrocarbons

Logistics information									
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight	



