EOS FLEX CUT B VV921

SLIGHTLY SHARP AND NON INTENSIVE WORK

Hand protection



Certifications and norms





Protects against risks









Specific benefits



Performance

- · Flexible reinforcements for added protection against impact and pinching
- The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)
- · SOFTnocut fiber provides excellent cut resistance

Applications

- Agriculture
- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive







EOS FLEX CUT B VV921

SLIGHTLY SHARP AND NON INTENSIVE WORK

Hand protection

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE X [0-5] CUT RESISTANCE 4 [0-4] TEAR RESISTANCE 2 [0-4] PIERCE RESISTANCE B [A-F] CUT RESISTANCE ISO 13997 P [P] IMPACT RESISTANCE (OPTIONAL)

Technical details

Color	Black
Mechanical glove kind	Knitted
Size	8, 9, 10
Glove family	Knitted coated glove
Coating level	Fully coated except wrist
Gauge	13
Number of layer	Single layer
Type of packaging	Sold individually
Special gloves kind	Impact
Benefits element	Reach, Vendor pack
Glove kind	Special glove







EOS FLEX CUT B VV921

SLIGHTLY SHARP AND NON INTENSIVE WORK

Safety gloves

Logistics information									
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight	



enjoy safety