

AN205200CD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hook



Certifications and norms

Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

· Certification above the maximum rated load of 100 kg: product certified at 140 kg



🦒 Easy to use

· NFC system guarantees traceability



Durability

· High webbing tenacity thanks to its weave and width




Compatibility

· Compatible with all kind of harnesses

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Heavy industry
- Light industry
- Maintenance



EN355

CE







AN205200CD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hook

Standards - Details

Technical details

Composition of the main support	Steel, Polyester
Length	2 m
With connector	yes
Ending	1 loop sewn thimble
Weight	1.1 kg
Type of equipment	Energy absorber in lanyard webbing
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection







AN205200CD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hook

Logistics information									
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight	
AN205200CD	Colourless	-	AN205200CD	0	0	10	1	11.25 kg	



