



Fall protection

# AN215200CDD

## ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks



### Specific benefits



#### Hygiene

- Harnesses and textiles can be washed with neutral soap



#### Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg



#### Easy to use

- NFC system guarantees traceability



#### Durability

- High webbing tenacity thanks to its weave and width



#### Compatibility

- Compatible with all kind of harnesses

### Applications

- **Public works**
- **Building**
- **Finishing works / Craftsmanship**
- **Heavy industry**
- **Light industry**
- **Maintenance**

### Certifications and norms

EN355





Fall protection

# AN215200CDD

## ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

### Standards - Details

### Technical details

Type of equipment	Energy absorber in lanyard webbing
Composition of the main support	Steel, Polyester
Length	2 m
With connector	yes
Connector (user side)	Screw carabiner, steel, opening 18mm
Connector (structure side)	Screw carabiner
Weight	1.6 kg
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Fall protection

# AN215200CDD

## ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN215200CDD	Colourless	-	AN215200CDD	3295249277260	0	10	1	16.65 kg