



Fall protection

AN245200PRR

ENERGY ABSORBING LANYARDS

Double lanyard with dielectric energy absorber made of elastic webbing, allowing protection against electrical risks



Specific benefits



Comfort

· Elastic strap lanyard for easy movement and safety



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

· Certification above the maximum rated load of 100 kg; product certified at 140 kg

· Strap with improved abrasion resistance and certified for use on sharp edges



Easy to use

· Ergonomic design facilitating user movements

· Automatic carabiners for secure and time-saving locking

Applications

- Agriculture
- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)

Certifications and norms

EN355



Protects against risks



Fall



Fall protection

AN245200PRR

ENERGY ABSORBING LANYARDS

Double lanyard with dielectric energy absorber made of elastic webbing, allowing protection against electrical risks

Standards - Details

Technical details

Type of equipment	Elastic strap with thimble loops
Composition of the main support	Plastic, Polyester
With connector	yes
Color	Black-Red
Connector (user side)	Small hook made of insulating material
SIZE	1.40 ► 2 m
Ending	2 sewn thimble loops
Connector (structure side)	2 big hooks made of insulating material
Lifespan from manufacturing	10 years
Weight	1,9 kg
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Fall protection

AN245200PRR

ENERGY ABSORBING LANYARDS

Double lanyard with dielectric energy absorber made of elastic webbing, allowing protection against electrical risks

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN245200PRR	Black-Red	1.40 2 m	AN245200PRR	3295249202316	13295249202313	5	1	10.994 kg