



Fall protection

L0007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Oil & Gas (extraction)
- Mining
- Power Energy

Certifications and norms

EN354



Protects against risks



Fall



L0007150CD

LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Standards - Details

Technical details

Type of equipment	Twisted rope
Composition of the main support	Glass-fibre
Length	1,5 m
Rope diameter	12 mm
With connector	yes
Color	White
Connector (user side)	Screw carabiner, steel, opening 18mm
SIZE	1.50 m
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing	10 years
Weight	0,850 kg
Fall arrest work situations	Restraint



Fall protection

LO007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
LO007150CD	White	1.50 m	LO007150CD	3660348006347	13660348006344	15	1	14.3 kg