



L0030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Certifications and norms

EN354



EN 795

TYPE B

Protects against risks



Fall



LO030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Standards - Details

Technical details

Color	Black-Orange
SIZE	1.50 m
Composition of the main support	Polyester
Length	1,5 m
Lifespan from manufacturing	10 years
Width	25 mm
Ending	2 sewn loops
Weight	0,187 kg
Type of equipment	Lanyard and anchorage point in tubular strap
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Width	0.9825 inch



LO030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
-----------	--------	------	-------------	-------	----------	----------------	---------------	--------